

FESTIVAL/CLUB TECHNICAL RIDER 2025

The following technical requirements for the artist **MOTHER OF MILLIONS** (MoM for short) are an integral part of their performance. If any or all of the specifications cannot be met, please **notify** the band and/or engineer **prior** to the show.

MoM are comprised of:

4x Artists – band contact is **Kostas** tel: 00306973357763

motherofmillionsband@gmail.com

1x FOH Sound Engineer – **Alex** tel: 0030 6977140775

unrealstudioz@gmail.com

1x Lights Engineer – **Panagiotis** tel: 0030 69422257762

panagiotis@napan.gr

Sound Check

Required sound check time is 1 hour.

Backline stuff that we carry:

Most Cymbals, Snare, Bass-drum pedal

Floor board modellers for both bass and guitar, no amps on stage

1x computer at drum riser running samples/live

Keyboard, through Soundgrid protocol

Keyboard Stand

Most of the mics

Backline Requirements

22"Bass Drum 12"rack-tom 16"floortom & 18"floortom 4 mic stands

Monitor Requirements

MoM are on their own in-ears, run from FOH.

FOH requirements

- We carry our own FOH/monitor desk. It is a Waves LV1 system. Provide a stable surface to put it on, and a CAT6 STP or SFTP (MUST BE SFTP AND NOT UTP!) cable run for the stage box. We carry our own cable, but it would make things easier if there was one already in place.
- The PA should be able to provide 105A with the master out meters around "unity", "zero", "0VU", call it what you will. That will ensure the proper headroom while keeping the show at "rock volume". Our show hovers around 100 dB LUFS.

Light Engineer requirements

A person in charge of the venue's lighting should be present and inform the band's lighting tech on available equipment and how to handle it.

Input List

| Channel | Instrument | Mic/DI |
|---------|-------------------------|---------------------|
| 01 | BassDrum in | Shure Beta91a(p48)* |
| 02 | BassDrum out | Beta 52a* |
| 03 | Snare | Heil pr22* |
| 04 | Snare bottom | Heil pr22* |
| 05 | Tom 1 | Heil Pr28* |
| 06 | Tom 2 | Heil Pr28* |
| 07 | Floor Tom | Heil Pr48* |
| 08 | _ | - |
| 09 | Overhead L | at3525(p48)* |
| 10 | Overhead R | at3525(p48)* |
| 11 | Ride | sdc mic |
| 12 | Hhat | sdc mic |
| 13 | Bass SL DI | XLR out* |
| 14 | Guitar SR1 | XLR out* |
| 15 | Guitar SR2 | XLR out* |
| 16 | Vox SR | Beta58 |
| 17 | Vox Center | Sm58* |
| 18 | Vox SL | Beta58 |
| 19 | Vox Drums | Beta58 |
| 19 | Audience mic center sdc | |

Items with an * are provided by us. The rest are venue provided mics.

Samples/keyboard played by the drummer are connected through the soundgrid network to the stage box. No analog audio is necessary.

Stage Plan

